



FLORIDA COLLECTION

CONTRACT • AUTOMOTIVE • UPHOLSTERY

Natural Leather

TECHNICAL DATASHEET

	TEST METHOD PRÜFVERFAHREN METHOD TEST MÉTODO DE PRUEBA	MEASUREMENT UNIT MAßEINHEIT UNIT OF MEASUREMENT UNIDAD DE MEDIDA	GUARANTEED GARANTIERT INSURED GARANTIZADA
BURNING BEHAVIOUR TO CIGARETTE AND MATCH FLAME BRANDVERHALTEN GGÜ. ZIGARETTENGLUT UND STREICHHOLZFLAMME COMPORTEMENT DE COMBUSTION DES CIGARETTES ET ALLUMETTES COMPORTAMIENTO FRENTE AL FUEGO Y LLAMA	BS 5852:1979 BS EN 1021-1-2:2006	 FIRE RETARDANT	PASS
COLOUR FASTNESS TO RUBBING DRY 500 CYCLES ABRIEBFESTIGKEIT TROCKEN 500 ZYKLEN RÉSISTANCE AUX FROTTEMENTS A SEC 500 CYCLES SOLIDEZ DEL COLOR AL FROTE A SECO 500 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
COLOUR FASTNESS TO RUBBING WET 150 CYCLES ABRIEBFESTIGKEIT NASS 150 ZYKLEN RÉSISTANCE AUX FROTTEMENTS HUMIDE 150 CYCLES SOLIDEZ DEL COLOR AL FROTE MOJADO 150 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
COLOUR FASTNESS TO RUBBING SWEAT 80 CYCLES ABRIEBFESTIGKEIT SCHWEIß 80 ZYKLEN RÉSISTANCE AUX FROTTEMENTS SUEUR 80 CYCLES SOLIDEZ DEL COLOR AL FROTE SUDOR 80 CICLOS	UNI EN ISO 11640:1998 ISO 11641 pH8	GREY SCALE	≥ 4
FLEXING ENDURANCE DRY 50.000 CYCLES BIEGEFESTIGKEIT TROCKEN 50.000 ZYKLEN RÉSISTANCE À LA FLEXION A SEC 50.000 CYCLES RESISTENCIA A LA FLEXIÓN A SECO 50.000 CICLOS	UNI EN ISO 5402		NO DAMAGE
FINISH ADHESION DRY HAFTUNG DER OBERFLÄCHENBEHANDLUNG TROCKEN ADHÉSION DU FILM A SEC ADHERENCIA DE ACABADO A SECO	UNI EN ISO 11644	N/cm	≥ 2
TEAR STRENGTH SINGLE EDGE TEAR REIßFESTIGKEIT HOSE EINKANTENRISS RÉSISTANCE AU DÉCHIREMENT BORD UNIQUE RESISTENCIA AL DESGARRO DESGARRO SIMPLE	UNI EN ISO 3377-1	N	≥ 20
COLOUR FASTNESS TO ARTIFICIAL LIGHT EXPOSITION ENERGY 16.000 kj/sqm UV-BESTÄNDIGKEIT EXPOSITIONS ENERGIE 16.000 kj/qm RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE ÉNERGIE D'EXPOSITION 16.000 kj/m ² SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL EXPOSICIÓN A ENERGÍA 16.000 kj/m ²	UNI EN ISO 105 B02 (MET.5)	BLUE SCALE	≥ 5

CLEAN AND CARE RECOMMENDATIONS

BRAZILIAN BOVINE ORIGIN, CORRECTED AND EMBOSSED GRAIN
PROTECTIVE TOP COAT, SOFT HANDLE AND SILKY MATTE FINISH
0.8 - 1.0 mm THICKNESS | 4.8 - 5.0 sqm AVERAGE

TO REMOVE DUST USE A VACUUM CLEANER.

AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.

ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.

WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

DELIVERY AND SHIPPING

24h DELIVERY TIME

E-STOCK SERVICE - READY TO SHIP

WORLDWIDE SHIPPING AVAILABLE